

# Legaltrek LXMD Technical Specifications

Model	
MD01	Single Target
MD03	3 Target
MD10	10 Target
Supported Source Formats	
SD Slot	SD, SD Pro, Mini SD*, Mini SD Pro*, Micro SD*, SDHC, WI-FI SD, Super HS SD (*Adapter Required)
USB Drive	All
CF Slot	CF I, CFII, IBM Micro Drive
MS Slot	MS, MS-Duo, MS Pro, MS Pro-Duo, MS MagicGate, MS Pro-Duo MagicGate etc.
MMC Slot	MMC, MMC Pro, MMC II, RS-MMC
Discs	DVD-ROM, DVD-Video, DVD+R, DVD+RW, DVD-R, CD-ROM, CD-I, Audio CD, Video CD, Bootable CD, Mixed-mode, CD, Multi-session CD, CD-Plus, Business Card CD, 3" Mini CD-R
Supported Discs	
	DVD+R, DVD+RW, DVD-R, DVD-RW, Dual Layer DVD±R, Business Card CD, 3" Mini CD-R, Standard CD-R/RW CD/DVD
Maximum Writing Speed	
	24X DVD±R, 8x Dual Layer DVD±R, 8x DVD+RW, 6x DVD-RW, 56x CD-R, 32x CD-RW
Operating Type	
	Stand Alone

<b>Writing Characteristics</b>	
<b>Writing Method</b>	DAO, TAO
<b>Backup Method</b>	Single Session/Multi-Session /Disc Spanning
<b>Disc Spanning</b>	Automatically distributes files to multiple target discs when copying a memory card with more data than one disc can hold
<b>Multi-Session Technology</b>	Backup multiple small capacity memory cards or USB drives on to one CD or DVD disc
<b>CD/DVD Copy to DVD</b>	Duplicates Audio CD, Video CD, DVD Video, and virtually any data disc in a matter of minutes without a computer
<b>System Memory</b>	
	64MB DDR2 (IDE-Interface) 512MB (SATA-interface)
<b>User Interface</b>	
	Four Button Operation
<b>Physical Interface</b>	On Device push buttons for recording with Start/Stop control
<b>Physical</b>	
<b>Display</b>	2 x 16 Backlit LCD
<b>Language</b>	English
<b>Operating Conditions</b>	41 to 104 deg. F (5 to 40 deg. C), 20 to 80% relative humidity (non-condensing)
<b>Power Supply</b>	Line Voltage: 100-240 VAC Frequency: 50-60 Hz
<b>Transport and Storage</b>	Max Operating Altitude: 3000 meters Max Transport altitude: 12,000 meters Storage Humidity 5 to 95% relative humidity (non-condensing)
<b>Regulatory</b>	EMI: FCC Class A, CE Mark Class A
<b>Warranty</b>	One year with free telephone support